



Premium Aluminum Trailers, Built for Work or Play

Phone: (204) 364-2785  
Email: [sales@stronghaul.com](mailto:sales@stronghaul.com)  
Address: 139144 Road 11E Arborg, MB, Canada  
Box 269 R0C 0A0

## SASD/SATD GEN1

**S**nowmobile Style, **A**luminum Frame, **S**ingle OR **T**andem Axle, **D**eck over Trailer



### -Standard Features and Equipment-

#### SASD-101x12-G1

#### SATD-101x22-G1

-6061 All Aluminum Frame	-6061 All Aluminum Frame
-3500lb Straight Axle, Idler	-3500lb Straight Axles, Elec. Brake
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape
-4-Pin Flat, Easy Pull Electrical Connector	-7-Pin RV Style Electrical Connector
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-Junction Box, Break-away Kit with Battery and Charger
-ST205/75R15 6-ply Radial Tires	-2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-ST205/75R15 6-ply Radial Tires
-LED Lighting Package	-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-LED Lighting Package
-A-Frame Mounted Jack Rated at 5K lbs	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone
-3/4" Douglas Fir/Larch Plywood Floor	-A-Frame Mounted Jack Rated at 5K lbs
-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch	-3/4" Douglas Fir/Larch Plywood Floor
-Pull Out Rear Ramp Rated at 1000lbs, 90" L x 51" W	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-6 x 2,000lb Lashing Rings , ZP	-Pull Out Rear Ramp Rated at 1000lbs, 90" L x 51" W
-2 x Superclamp Hold Down Bars with 2' of adjustable Supertrac	-9 x 2,000lb Lashing Rings , ZP
-Full Length 3" High Side Rail	-4 x Superclamp Hold Down Bars with 2' of adjustable Supertrac
-Underside Spare Tire Mount	-Full Length 3" High Side Rail
-Deck to Ground Height: 30"	-Underside Spare Tire Mount
-Ground to Coupler Height: 21" When Level	-Deck to Ground Height: 30"
-GVWR: 2,990lbs (3,500lbs with additional electric brake option)	-Ground to Coupler Height: 21" When Level
	-GVWR: 7000lbs

### -Available Sizes-

Description	STD. Payload	Dry Wt.
SASD-101x12-G1	2,190 lbs	800 lbs
SATD-101x22-G1	5,560 lbs	1440 lbs

### -Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Extra Lashing Rings 2k lb
Superglide Decking Upgrade
GEN1 Spray Shield