

UASS-24 (60x10 Displayed)

Utility Style, Aluminum Frame, Single Axle, Solid side Trailer with 24" Sides



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-22.5" Side Height (Deck to top of Flange)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch
-3500lb Straight Axle, Idler	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-2,000lb Lashing Rings, ZP (4 rings on 8' models, 6 on 10', 8 on 12', and 10 on 14')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes-

Description	STD. Payload	Dry Wt.
UASS-60x10-24	2,192 lbs	798 lbs
UASS-60x12-24	2,114lbs	876 lbs
UASS-66x10-24	2,122 lbs	868 lbs
UASS-66x12-24	2,014 lbs	976 lbs
UASS-76x12-24	1,960 lbs	1030 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, Solid Side, 60"
Spray Shield, Solid Side, 66"
Spray Shield, Solid Side, 76"
Extra Lashing Rings 2k lb
Jack Caster Wheel
Side Mount Pivot Jack
A-Frame Mounted, Lockable Handle Tool Box
Electric Braking Axle Upgrade

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.