



Premium Aluminum Trailers, Built for Work or Play

Phone: (204) 364-2785
Email: sales@stronghaul.com
Address: 139144 Road 11E Arborg, MB, Canada
Box 269 R0C 0A0

UATS (76x14 Displayed)

Utility Style, Aluminum Frame, Tandem Axle, Solid side Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-A-Frame Mounted Jack Rated at 5K lbs
-13.5" Side Height (Deck to top of Flange)	-2x10 Douglas Fir/Larch Plank Floor
-Tandem 3500lb Drop Axles, Electric Brakes	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Folding Rear Ramp rated at 3000lbs
-7-Pin RV Style Electrical Connector	-Ramp Unfolded Length: 54" L x 71" W (Ramp Width is trailer size - 5.00")
-Junction Box, Break-away Kit with Battery and Charger	-Ramp Folds Down onto Deck
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings , ZP(6 rings on 12' models, 6 on 14', 6 on 16', and 8 on 18')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs

-Available Sizes-

Description	Payload	Dry Wt.
UATS-76x12	5,920 lbs	1080 lbs
UATS-76x14	5,860 lbs	1140 lbs
UATS-76x16	5,740 lbs	1260 lbs
UATS-82x12	5,880 lbs	1120 lbs
UATS-82x14	5,805 lbs	1195 lbs
UATS-82x16	5,720 lbs	1280 lbs
UATS-82x18	5,635 lbs	1365 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Drop In Rear Panel, 76"
Drop In Rear Panel, 82"
Spray Shield, SS 76"
Spray Shield, SS, 82"
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
Stabilizer Stands, Drop Leg
2-5/16" Adjustable Coupler
A-Frame Mounted, Lockable Handle Tool Box