STRONGhaul
Aluminum Trailers

UATS

THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design



SMART DESIGN

Purpose Built • Work Ready

STRONGhaul
Aluminum Trailers

UATS





Address: 139144 Road 11E
Arborg, MB, Canada
P.O. Box 269 R0C 0A0

www.stronghaul.com

STRONGhaul
Aluminum Trailers

UATS

Utility Style, Aluminum Frame, Tandem Axle, Solidside Trailer



UATS-76x12-7K
UATS-76x14-7K
UATS-76x16-7K
UATS-82x12-7K
UATS-82x14-7K
UATS-82x16-7K
UATS-82x18-7K

PREMIUM ALUMINUM TRAILERS

Built for Work or Play

STRONGhaul
Aluminum Trailers

UATS

Utility Style
Aluminum Frame
Tandem Axle
Solidside Trailer

Available Sizes

Description	Payload	Dry Weight
UATS-76x12-7K	5,920 lbs	1080 lbs
UATS-76x14-7K	5,860 lbs	1140 lbs
UATS-76x16-7K	5,740 lbs	1260 lbs
UATS-82x12-7K	5,880 lbs	1120 lbs
UATS-82x14-7K	5,805 lbs	1195 lbs
UATS-82x16-7K	5,720 lbs	1280 lbs
UATS-82x18-7K	5,635 lbs	1365 lbs



ALL ALUMINUM CONSTRUCTION
Light • Strong • Durable
www.stronghaul.com

Standard Features

- Frame: Aluminum 6061
- Side Height: 13.5" (Deck to top of Flange)
- Axle: 3500lb Drop Axles, Electric Brakes
- Axle Brackets: .250" Galvanized and Taped
- Harness Plug: 7-Way RV-Style Connector with Break-away Kit
- Coupler: 2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape
- Tires: ST205/75R15 6-ply Radial
- Wheels: Black Mod. Steel, R15", 5 lug on 4.5" BHP
- Lighting: LED Lighting Pkg with Sealed Harness
- Jack: 5,000lb, A-Frame Mounted
- Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks
- Safety Chains: 3/8" x 35" Chains, 16.2K lb Rating, with Safety Latch
- Ramp: Folding Rear Ramp rated at 3000lbs
- Ramp Unfolded Length: 54" L x 71" W
- Ramp Folds Down onto Deck
- Lashing Rings: 4,000lb, ZP (6 rings on 12', 14', 16' models, and 8 on 18' models)
- Spare Tire Mount: Front, or on side with toolbox
- Deck to Ground Height: 18"
- Ground to Coupler Height: 15" When Level
- GVWR: 7,000 LBS

Available Options

- Aluminum Wheel Upgrade PKG
- Spare Wheel, Steel
- Spare Wheel, Aluminum
- Drop In Rear Panel, 76"
- Drop In Rear Panel, 82"
- Spray Shield, Solid Side 76"
- Spray Shield, Solid Side, 82"
- Extra Lashing Rings 4k lb
- Recessed Lashing Rings 6k lb
- Jack Caster Wheel
- Side Mount Pivot Jack
- Stabilizer Stands, Drop Leg
- Adjustable Coupler 2-5/16"
- Toolbox, A-Frame Mounted, Lockable



PREMIUM ALUMINUM TRAILERS
Built for Work or Play